

<b>Project Information</b>	
Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

The EnviroLux 23 Watt LED Mini Glass Wall Pack luminaire is designed to replace HID lighting systems between 40w to 1000w MH or HPS. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 10 to 15 feet can be used based on light level and uniformity requirements.

**SPECIFICATIONS AND FEATURES:**

**HOUSING:**

Die Cast Hinged and Gasketed Aluminum Door Frame and Housing with 1/2" Coin Plugs. Nickel-Plated Stainless Steel Hardware. Photocell Adaptable.

**FINISH:**

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

**LENS:**

Bottom: Tempered Clear Flat Glass Lens,  
Top: Optional Oval Molded Tempered Clear Glass Lens.

**MOUNTING OPTIONS:**

Mount Directly Over a 4" Recessed Outlet Box, Includes Easy-Hang "Two Hands Free" Wall Mounting Bracket with Built-In Level

**EnviroLux LED Engine:**

**201LPW, 83CRI**, Silicone Coated Aluminum Core Boards - Water and Humidity Proof

**WATTAGE:**

**23K** = Array: 23 System Watts: **Lumens - 4160**  
(100-250W HID or Induction Equivalent.)

**DRIVER:**

Programmable Driver, 120-277V, 50/60Hz; Dimmable Driver.


**Listing and RATINGS:**

CSA Listed. Operating in Ambient Temperatures: -40°C to + 50°C IP67 Sealed LED Compartment.



**Dimensions**

**Width (D)** 6 3/4" (172mm)  
**Length (B)** 5 1/4" (133mm)  
**Height (A)** 11" (280mm)



**EnviroLux 23 Watt LED Mini Glass Wallpack**

**Ordering Information Example:**  
EESWP12QF1X23U5K

Scan to watch our Made in USA video



Model	Part Suffix	Wattage	Driver	CCT	Lens	Mounting	Options
EES	WP12QF	1x23	U=120-277V	4K=4000K 5K=5000K			
				GL=Opaque			
				4" Recessed Outlet Box Easy Hang Mounting Bracket			
				<b>SF</b> =Single Fuse <b>DF</b> =Double Fuse <b>PC1-PC2</b> =Universal Button Photo Cell 120-277 <b>SP</b> =Surge Protection 6kv standard, 10kv optional			



EnviroLux Unifi Mesh Passport can operate up to 500 fixtures on a wireless network from anywhere in the world.



## ***EnviroLux LED Mini Glass Wallpack***



***Button Photocell  
(PC1, PC2)***