



# **LED Pro Series**

EESWH15QF1X37U5KC

10

	— Droject Information ———			
Project Name:	<ul> <li>Project Information ——</li> </ul>	Fixture Type:		
Complete Catalog #:		Date:		

Comments:

The EnviroLux 45 Watt LED Medium Semi Full Cutoff Wall Pack luminaire is available with a choice of optical distributions designed to replace HID lighting systems up to 400 MH or HPS. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 15 to 24 feet can be used based on light level and uniformity requirements.

#### **SPECIFICATIONS AND FEATURES:**

#### HOUSING:

Die Cast Hinged and Gasketed Aluminum Front Frame and Housing with ½" Coin Plugs. Nickel-Plated Stainless Steel Hardware. Photocell Adaptable.

#### FINISH:

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

LENS:

#### Borosilicate Glass Lens.

#### **MOUNTING OPTIONS:**

Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use  $\frac{1}{2}$ " Surface Conduit.

#### EnviroLux LED Engine: 201 LPW, > 80 CRI

#### WATTAGE:

**45W**=Array: 45 System Watts: Lumens - 8,140 (400W HID or Induction Equivalent.)

#### **DRIVER:**


Programmable Driver, 120-277V, 50/60Hz; Dimmable Driver.

#### Listing and RATINGS:

CSA Listed. Operating in Ambient Temperatures: -40°C to + 50°C IP67 Sealed LED Compartment.



	10
Contraction of the	
10000	
and the second second	
Sec. 2	
Contract of	
1000	
2	
11	
1	
-	A DECEMBER OF THE OWNER OF
1000	
	ANNUM



в

### EnviroLux LED 45 Watt Semi Full Cutoff Wallpack

**Dimensions** 

Width (D)

Length (B)

Height (A)



ഹ

Ordering Information Example: EESWH15QF1X37U5KC

### Scan to watch our Made in USA video

Model EES	Part Suffix WH15QF	Wattage 1x37	Driver U	CCT 3K=3000K (Optional) 4K=4000K (Optional) 5K=5000K (Standard)	Lens	Mounting	Options
				C=Clear Borosilio	cate		
					4" Recessed Ou 1/2" Surface Cor		
	43	unifin passport			e Fuse Cell 120-277		
		Unifi Mesh Passport can operat a wireless network from anywh		M1=Motion M2=Motion WG=Wire (	n Sensor, IR for n n Sensor, IR for n Guard ergency Battery E	andard, 10kv option nounting heights of 2 nounting heights of 7 Backup	20ft to 35ft

#### 1304 NE 154th Street, Suite 102 • Vancouver, WA 98685 • Toll-Free: 800-914-8779 For more information, go to www.envirolux.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

## EnviroLux Small Semi Full Cutoff Wallpack Options





EMB