

0 25°C 290,000 Hours

LED Pro Series

HE-ENV-10W-LED-LFL-AMBER-600NM-PS-UNV-ST

	Droject Information			
Project Name:	— Project Information —	Fixture Type:		
Complete Catalog #:		Date:		

The EnviroLux Mini Amber Stealth is available with a wide choice of mounting configurations and optical distributions designed to replace HID lighting systems from 70w to 150w. Typical area lighting applications include retail centers, industrial parks, airports, and office buildings, close to beaches where Amber environmental lighting codes apply. Mounting heights of 14 to 20 feet can be used based on light level and uniformity requirements.

SPECIFICATIONS AND FEATURES:

HOUSING:

Comments:

Die Cast Aluminum Housing and Front Frame, Integral Heat Sinking and Driver Compartment. Photocell Adaptable. Nickel-Plated Stainless Steel Hardware.

FINISH:

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

LENS:

Tempered Clear Flat Glass Lens or Tempered Clear Flat Prismatic Glass Lens.

MOUNTING OPTIONS:

Mounts with Stealth Arm. Adjustable Slipfitter. 23/8" Diameter Mounting Arm Adapter, Yoke, Two-Piece Bracket or Easy Hang Wall Bracket (Factory Installed).

Complete Units Ordering Information Example: HE-ENV-10W-LED-LFL-AMBER-600NM-PS-UNV-ST

HE-ENV

EnviroLux LED Engine:

135 LPW, 600NM, Silicone Coated Aluminum Core Boards - Water and Humidity Proof

WATTAGE:

10W=Array: 10 System Watts: Lumens:1,282 (50W HID or Induction Equivalent.)

DRIVER:


Programmable Driver, 120-277V, 50/60Hz; Dimmable Driver.

Listing and RATINGS:

CSA Listed. Operating in Ambient Temperatures: -40°C to + 50°C IP67 Sealed LED Compartment.







Dimensions

Width (D)	9½" (240mm)
Length (B)	11¾ (299mm)
Height (A)	3%″ (92mm)

EnviroLux 600NM AMBER Mini Stealth



Scan to watch our Made in USA video

Model HE-ENV	Part Suffix 10W-LED-LFL- AMBER-600NM-PS-UNV-ST	Driver Wattage U=120-277V 10	CCT 600NM AMBER	Lens	Mounting	Options	
			GL=Glare Shield				
	Unif passport 20 make the marter	S NI		STY=Stealth SSB=Two-Pie	tter Mounting Arm Adapter th Yoke Piece Swivel Bracket sy-Hang Wall Bracket		
		assport can operate up to 500 etwork from anywhere in the world.	M2=Motion Se R3=3-Pin Twis	tection ensor, IR for mount ensor, IR for mount it Lock Photocell R II C136.41—2013 norting cap	ting heights of 20ft to ting heights of 18ft o Receptacle Twist Lock Photoce	r less	

1304 NE 154th Street, Suite 102 • Vancouver, WA 98685 • Toll-Free: 800-914-8779 For more information, go to www.envirolux.com

Data is based upon tests performed by in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

EnviroLux Mini Stealth AMBER 600NM LED Flood Light Mounting and EPA

ADDITIONAL MOUNTING OPTIONS



Shown with "STA" Stealth Mounting Arm, Stealth Die-Cast Mounting Arm, Bronze Powdercoat Finish, Includes Hardware. Mounts Directly to Square Poles.



Shown with "ALMAA" Pole Mounting Arm Adaptor, Die-Cast Adaptor for 2%" Horizontal Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.



Shown with "STY" Yoke, Stamped Heavy-Duty Steel Yoke, Bronze Powdercoat Finish, Includes Hardware.



Shown with "SSF" External Mount SlipFitter, External Mount Die-Cast Adjustable Slipfitter for 2%" Tenons, Bronze Powdercoat Finish, Includes Hardware.



Shown with "SSB" Two-Piece Swivel Bracket, Two-Piece Stamped Steel Adjustable Bracket, Bronze Powdercoat Finish, Includes Hardware.



Shown with "KHEH" Easy-Hang Wall Bracket, Die-Cast Easy-Hang Wall Bracket, Bronze Powdercoat Finish, Includes Hardware.

Shown with side mount arm **EPA (Effective Projected Area)**

Configuration	EPA (Sq. Ft.)	Weight Lbs.)	Configuration	EPA (Sq. Ft.)	Weight Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA Sq. Ft.)	Weight Lbs.)
	0.35	11 Lbs	2@180° Mount	0.70	22 Lbs	3 @90° Mount	0.77	33 Lbs	8 -∳- 8 4@90° Mount	0.77	44 Lbs
			•- 2@90° Mount	0.48	22 Lbs	₽ 3 @120° Mount	0.70	33 Lbs			

			_					
	Mounting Acc (Order separa	essories tely, Field installed)	Accessorie (Order sepa	s arately, Field installed)		Replacement Parts (Order separately, Field installed)		
	EES20RPZ	Die-Cast Adaptor for 3" to 4" Round	EES-P18140	110-120VAC Instant Twist Lock	EES-STGL	Tempered Clear Flat Glass Lens.		
		Poles, Bronze Powdercoat Finish. Use with Stealth Mounting Arm	FE0 040440	Photocell	EES-STGLP	Tempered Prismatic Flat Glass Lens.		
EESST20RPZ EESST20WMZ		only.	EES-P18142	110-277VAC Instant Twist Lock Photocell	EES-AZ	Stealth Die-Cast Mounting Arm, Bronze Powdercoat Finish, Includes		
	EES20WMZ	Die-Cast Wall Mount Adaptor, Bronze Powdercoat Finish. Use with STA Kitty Stealth Mounting	EES-P18150	120VAC Time Delay Twist Lock Photocell		Hardware. Mounts Directly to Square Poles.		
	EESPTSB1SZ	Arm only. Single Pole Tenon Spoke Bracket,	EES-P18152	EES-P18152 277VAC Time Delay Twist Lock Photocell		External Mount Die-Cast Adjustable Slipfitter for 2%" Tenons, Bronze		
EESSTPTSB1SZ EESPTSB290SZ		2¾" Horizontal Mounting Arm, Bronze Powdercoat Finish, Includes	EES-P18131	Twist Lock Non-Shorting (Open) Cap Disconnects Service to		Powdercoat Finish, Includes Hardware.		
	Hardware. EESPTSB290SZ Twin Pole Tenon Spoke Bracket, 2%" Horizontal 90° Mounting Arms,			Fixture for Temporary or Permar Disabling (Fixture Always Off). IF 480V Maximum.		2 Die-Cast Adaptor for 2%" Horizontal Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.		
EESPTSB2180SZ EESPTSB390SZ*		Bronze Powdercoat Finish, Includes Hardware.	EESP18132	Twist Lock Shorting Cap Provide Fixed Service to Fixture (Fixture		Stamped Heavy-Duty Steel Yoke, Bronze Powdercoat Finish, Includes		
EESP136210052 EESP13639052	EESPTSB2180- SZ	Twin Pole Tenon Spoke Bracket, 2¾" Horizontal 180° Mounting Arms,		Always on). IP65, Rated Load 7200w Tungsten.		Hardware.		
		Bronze Powdercoat Finish, Includes Hardware.	EES-ACCHS G1Z	Installing Sensors or Other Light	ing	Two-Piece Stamped Steel Adjustable Bracket, Bronze Powdercoat Finish, Includes Hardware.		
	EES-PTSB 390SZ*	Triple Pole Tenon Spoke Bracket, 2%" Horizontal 90° Mounting Arms,		Control, Bronze Powdercoat Fin	ish. EES-EHZ	Die-Cast Easy-Hang Wall Bracket, Bronze Powdercoat Finish, Includes Hardware.		
EESPTSB3120SZ* EESPTSB490SZ*	5500 <u>2</u>	Bronze Powdercoat Finish, Includes Hardware.	EES25GSZ	Aluminum House Side Shield, Bronze Powdercoat Finish, Inclu Hardware.	ides			
	EESPTSB3120- SZ	Triple Pole Tenon Spoke Bracket, 2%" Horizontal 120° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.						
EESACCHSG1Z EES25GSZ	EESPTSB490SZ*	⁴ Quad Pole Tenon Spoke Bracket, 2%" Horizontal 90° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.	EESP181		ES-P18150, E	ES-P18131 EES-P18130		
	*Special order ite	m. Lead time three weeks.		EES-P18142 E	ES-P18152			