



LED Pro Series

ENV-90W-LED-DE-RETKIT-PS-UNV

(Example only of custom LED insert)

93 Percent Efficient LED Drivers

Programmable,

Digital, Wide-Range Ajustable Current & Dimming

Type TL Rated

Waterproof LED Engines

135 Lumens Per Watt

7 Year Warranty

Project Name:	— Project Information —	Fixture Type:	
Complete Catalog #:		Date:	-
Comments:			-

The EnviroLux 90 Watt Custom Fit AMBER LED Retro Fit Kit is designed to replace HID lighting systems between 250w to 400w MH or HPS. Typical existing HID lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of up to 30 feet can be used based on light level and uniformity requirements.

SPECIFICATIONS AND FEATURES:

Custom Fit LED inserts produced in any shape or size that match the reflector inside your existing HID fixture. Simply send us an existing reflector and we will custom design the exact fit LED replacement. Replaces HID Wallpacks, Area Floodlights, Canopy, High Bay and Low Bay fixtures up to 400 Watt.

- Up to 135 Lumens Per Watt
- Unifi EnviroLux Wireless Optional
- Tight Bin LED Range (No Color Shift in LEDS)
- 6 KV Surge Protection in LED Driver
- * 10 KV Auxiliary Surge Protection Between Power and Driver - Optional
- Programmable LED Drivers
- Silicone Waterproof Engines
- Products Manufactured and Shipped in 24-48
- Hours
- 7 Year Warranty

ENV


DLC Model Number:

EnviroLux 90 Watt Double Engine AMBER Retrofit Kit

ENV-90W-LED-DE-RETKIT-PS-UNV



Scan to watch our Made in USA video



1304 NE 154th Street, Suite 102 • Vancouver, WA 98685 • Toll-Free: 800-914-8779 For more information, go to www.envirolux.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

EnviroLux LED Engine: PW, 83CRI, Silicone Coated Aluminum Core Boards - Water and Humidity Proof

WATTAGE:

90W=Array: 90 System Watts: Lumens-12,150 (250W - 400W HID or Induction Equivalent.)

DRIVER:

Programmable Driver, 120-277V, 50/60Hz; Dimmable Driver.

Listing and RATINGS:

Listed for operating in ambient temperatures: -40°C to + 50°C IP67 Sealed LED Compartment.

