



LED Pro Series

EESKH25-LED-PS-UNV-114W-XXXX

	— Drojact Information —			
Project Name:	— Project Information —	Fixture Type:		
Complete Catalog #:		Date:		
Comments:				

The EnviroLux Small Slimline Flood Light is available with a wide choice of mounting configurations and optical distributions designed to replace HID lighting systems from 150w to 400w. Typical area lighting applications include retail centers, industrial parks, airports, and office buildings, close to beaches where Amber environmental lighting codes apply. Mounting heights of 14 to 25 feet can be used based on light level and uniformity requirements.

SPECIFICATIONS AND FEATURES:

HOUSING:

Die Cast Aluminum Housing and Front Frame, Integral Heat Sinking and Driver Compartment. Photocell Adaptable. Nickel-Plated Stainless Steel Hardware

FINISH:

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

LENS:

EES

Tempered Clear Flat Glass Lens or Tempered Clear Flat Prismatic Glass Lens.

MOUNTING OPTIONS:

Mounts with Stealth Arm, Adjustable Slipfitter, 23/8" Diameter Mounting Arm Adapter, Yoke, Two-Piece Bracket or Easy Hang Wall Bracket (Factory Installed).

EnviroLux LED Engine:

192 LPW, 83CRI, Silicone Coated Aluminum Core Boards - Water and Humidity Proof

WATTAGE:

114W=Array: 114 System Watts: Lumens:20,793 (150-400W HID or Induction Equivalent.)

DRIVER:


Programmable Driver, 120-277V, 50/60Hz; Dimmable Driver.

Listing and RATINGS:

CSA Listed. Operating in Ambient Temperatures: -40°C to + 50°C IP67 Sealed LED Compartment.




0



Dimensions

Width (D) 133/3"" (340mm) Length (B) Height (A) 35/s" (92mm)



Scan to watch our Made in USA video

Wattage Model Part Suffix Driver ССТ Mounting Options Lens EES KH25-LED-PS UNV=120-277V 114W 2700K 3000K 3500K 4000K 5000K CL=Clear STA=Stealth Arm SSF= Slipfitter ALMAA - Mounting Arm Adapter STY=Stealth Yoke SSB=Two-Piece Swivel Bracket KHEH=Easy-Hang Wall Bracket unifi NM=No Mount S make life smarter UNIFI=EnviroLux Unifi Wireless SF=Single Fuse EnviroLux Unifi Mesh Passport can operate up to 500 **DF**=Double Fuse **SP**=Surge Protection fixtures on a wireless network from anywhere in the world. M1=Motion Sensor, IR for mounting heights of 20ft to 35ft M2=Motion Sensor, IR for mounting heights of 18ft or less R3=3-Pin Twist Lock Photocell Receptacle R7=7-Pin ANSI C136.41-2013 Twist Lock Photocell Receptacle with P18132 shorting cap 480v=480Volt

EnviroLux Small Slimline Flood Light

1304 NE 154th Street, Suite 102 • Vancouver, WA 98685 • Toll-Free: 800-914-8779 For more information, go to www.envirolux.com

Data is based upon tests performed by in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

EnviroLux Small Slimline Flood Light Mounting and EPA

ADDITIONAL MOUNTING OPTIONS



Shown with "STA" Stealth Mounting Arm, Stealth Die-Cast Mounting Arm, Bronze Powdercoat Finish, Includes Hardware. Mounts Directly to Square Poles.



Shown with "ALMAA" Pole Mounting Arm Adaptor, Die-Cast Adaptor for 2%" Horizontal Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.



Shown with "STY" Yoke, Stamped Heavy-Duty Steel Yoke, Bronze Powdercoat Finish, Includes Hardware.



Shown with "SSF" External Mount SlipFitter, External Mount Die-Cast Adjustable Slipfitter for 2%" Tenons, Bronze Powdercoat Finish, Includes Hardware.



Shown with "SSB" Two-Piece Swivel Bracket, Two-Fiece Stamped Steel Adjustable Bracket, Bronze Powdercoat Finish, Includes Hardware.



Shown with "KHEH" Easy-Hang Wall Bracket, Die-Cast Easy-Hang Wall Bracket, Bronze Powdercoat Finish, Includes Hardware.

EPA (EFFECTIVE PROJECTED AREA) SHOWN WITH SMALL Stealth ARM MOUNTING

Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)
•-	0.60	15 Lbs	2@180° Mount	1.20	30 Lbs	3@90° Mount	1.32	45 Lbs	₽•• • ■ 4@90° Mount	1.32	60 Lbs
			•- 2@90° Mount	0.82	30 Lbs	↓ 3@120° Mount	1.20	45 Lbs			

	Mounting Accessories (Order separately, Field installed)		Accessories (Order sepa	s ırately, Field installed)		Replacement Parts (Order separately, Field installed)		
	EES20RPZ	Die-Cast Adaptor for 3" to 4" Round	EES-P18140	110-120VAC Instant Twist Lock	EES-STGL	Tempered Clear Flat Glass Lens.		
		Poles, Bronze Powdercoat Finish. Use with Stealth Mounting Arm	FF0 D10142	Photocell EES-P18142 110-277VAC Instant Twist Lock		Tempered Prismatic Flat Glass Lens.		
EESST20RPZ EESST20WMZ		only.	EES-P10142	Photocell	EES-AZ	Stealth Die-Cast Mounting Arm, Bronze Powdercoat Finish, Includes		
	EES20WMZ	Die-Cast Wall Mount Adaptor, Bronze Powdercoat Finish. Use with STA Kitty Stealth Mounting	EES-P18150	120VAC Time Delay Twist Lock Photocell		Hardware. Mounts Directly to Square Poles.		
		Arm only.	EES-P18152	277VAC Time Delay Twist Lock Photocell	EES-SSFZ	External Mount Die-Cast Adjustable Slipfitter for 23%" Tenons, Bronze		
EESSTPTSB1SZ EESPTSB290SZ	EESPTSB1SZ	Single Pole Tenon Spoke Bracket, 2 ³ / ₈ " Horizontal Mounting Arm,	EES-P18131	Twist Lock Non-Shorting (Open)		Powdercoat Finish, Includes		
		Bronze Powdercoat Finish, Includes Hardware.		Cap Disconnects Service to	550414447	Hardware.		
	EESPTSB290SZ	Twin Pole Tenon Spoke Bracket, 2%" Horizontal 90° Mounting Arms,		Fixture for Temporary or Permanent Disabling (Fixture Always Off). IP65, 480V Maximum.	EESALMAAZ	Die-Cast Adaptor for 2%" Horizontal Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.		
EESPTSB2180SZ EESPTSB390SZ*		Bronze Powdercoat Finish, Includes Hardware.	EESP18132	Twist Lock Shorting Cap Provides Fixed Service to Fixture (Fixture	EES-STYZ	Stamped Heavy-Duty Steel Yoke, Bronze Powdercoat Finish, Includes		
		Twin Pole Tenon Spoke Bracket, 2%" Horizontal 180° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.		Always on). IP65, Rated Load 7200w Tungsten.		Hardware.		
				Die Cast Accessory Housing for	EES-SSBZ	Two-Piece Stamped Steel Adjustable Bracket, Bronze Powdercoat Finish, Includes Hardware.		
	EES-PTSB	Triple Pole Tenon Spoke Bracket,	G1Z	Installing Sensors or Other Lighting Control, Bronze Powdercoat Finish.				
	390SZ*	2%" Horizontal 90° Mounting Arms,	EES25GSZ	Aluminum House Side Shield.	EES-EHZ	Die-Cast Easy-Hang Wall Bracket, Bronze Powdercoat Finish, Includes		
EESPTSB3120SZ* EESPTSB490SZ*		Bronze Powdercoat Finish, Includes Hardware.		Bronze Powdercoat Finish, Includes Hardware.		Hardware.		
	EESPTSB3120- SZ	Triple Pole Tenon Spoke Bracket, 2%" Horizontal 120° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.				.		
EESACCHSG1Z EES25GSZ	EESPTSB490SZ*	Quad Pole Tenon Spoke Bracket, 2%" Horizontal 90° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.	EESP181		-P18150, L -P18152	EES-P18131 EES-P18130		
	*Special order iter	n. Lead time three weeks.						